

## True Flat Touch Monitor Series

### Features

- Touch Function Supported
- USB or VGA Interface Available
- Durable Die-casting Aluminum base design
- Easy for installation - One USB cable needed
- Best choice for space limited retail/hospitality settings
- True Flat designed to suit harsh environment
- Spill proof & Anti-dust



**M363**



**M364**



**M365**



True flat design



Wall mount available



VGA interface available



USB interface available



Die-casting base design

### Specifications

Model	M363RD	M363RC	M364RD	M364RC	M365RD	M365RC
Display Size	7" wide		8.4"		10.4"	
Optimal Resolution	800 * 480		800 * 600		800 * 600	
Panel Brightness	200 cd/m <sup>2</sup> (typ)		230 cd/m <sup>2</sup> (typ)	180 cd/m <sup>2</sup> (typ)	300 cd/m <sup>2</sup> (typ)	180 cd/m <sup>2</sup> (typ)
Contrast Ratio	500:1 (typ)		600:1 (typ)		500:1 (typ)	
Response Time	25 ms (typ)		8 ms (typ)		30 ms (typ)	
Viewing Angle(L / R / U / D)	70 / 70 / 50 / 60		75 / 75 / 60 / 70		75 / 75 / 50 / 60	
Tilt Angle	35°C(V) / 70°C(H) w/pole		N/A		N/A	
Input Video signal	VGA	USB B Type	VGA	USB B Type	VGA	USB B Type
Touch	Resistive Touch, USB interface					
Power consumption	6W	2.5W	6W	2.5W	8W	2.5W
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical :56.3Hz~75Hz					
Power supply	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%
Temperature	Operating : 0°C~40°C ; Storage : -10°C~50°C					
Humidity	Operating : 20%~80% ; Storage : 10%~90%					
Weight	1.2 Kg		1.4Kg		1.5Kg	
Physical Dimension WxHxD(mm)	184.5*170.5*142		202*189.7*142		244*210.3*142	
Optional	White, Wall Mount Kit , Stand					

Product specification subject to change without prior notice.

#### OTEK SYSTEM CO., LTD.

Address: 6F, 30 Sinjhong Rd., Neihu District, Taipei 114, Taiwan Tel: 886-2-7720-1688 Fax: 886-2-7721-2188

http://www.oteksys.com sales@oteksys.com

M360a-1110



©2011 OTEK System Co., Ltd. All rights reserved.